



# PRO712 REDUCER

PRODUCT SUBMITTAL

## TECHNICAL DATA

<b>ASTM E84 - Surface Burning</b>	Class A
<b>ASTM E648 (NFPA 253) - Critical Radiant Flux</b>	Class 1, $\geq 0.45 \text{ W/cm}^2$
<b>ASTM E662 (NFPA 258) - Smoke Density</b>	Passes, $\leq 450$
<b>Acclimation Time</b>	48 Hours, see installation instructions for details
<b>Service &amp; Storage Temperature</b>	65° - 85° F, see installation instructions for details

<b>Sustainability Information</b>	Contributes to LEED v4/4.1 Meets CA 01350 Requirements FloorScore Certification*
-----------------------------------	--

<b>Warranty</b>	1 Year Commercial, see warranty document for details
-----------------	--

<b>Recommended Adhesives</b>	Excelsior EN-610, Epoxy Nose Filler Excelsior C-630, Contact Adhesive Excelsior U-705, Urethane Wet-Set
------------------------------	---

<b>Adhesives Not Recommended</b>	Pressure Sensitive and Tapes can allow the material to shrink if stretched during installation
----------------------------------	--

## PRODUCT DESCRIPTION

Reducer is designed to reduce tile edges of .375" to nothing.

